

Spindle Bearings

✖							
✖							
Bearing No.	Suffix Explanation	Mass(kg)	d	D	B	Basic Load Rating(N) Cr	Cor
B7000-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.01919	10	26	8	4207.5	2059.2
B7000-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.01919	10	26	8	4009.5	1980
B7001-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.02121	12	28	8	4702.5	2574
B7001-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.02121	12	28	8	4504.5	2475
B7002-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.0303	15	32	9	6138	3366
B7002-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.0303	15	32	9	5940	3217.5
B7003-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.03939	17	35	10	8563.5	4851
B7003-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.03939	17	35	10	8217	4702.5
B7004-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.06868	20	42	12	10296	5940
B7004-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.06868	20	42	12	9900	5643
B7005-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.08181	25	47	12	14454	9058.5
B7005-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.08181	25	47	12	13563	8563.5
B7006-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.1212	30	55	13	14850	10098
B7006-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.1212	30	55	13	14157	9702
B7007-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.16059	35	62	14	18810	13563
B7007-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.16059	35	62	14	18117	12771
B7008-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.19796	40	68	15	20196	15840
B7008-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.19695	40	68	15	19404	14850

Spindle Bearings

B7009-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.2424	45	75	16	27225	20988
B7009-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.2424	45	75	16	26235	19800
B7010-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.26159	50	80	16	28215	22572
B7010-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.26058	50	80	16	26730	21384
B7011-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.37774	55	90	18	37620	30690
B7011-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.37673	55	90	18	35640	28710
B7012-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.40097	60	95	18	38610	33165
B7012-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.39996	60	95	18	36135	31185
B7013-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.42521	65	100	18	39600	35145
B7013-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.4242	65	100	18	37620	33165
B7014-C-T-P4S	Contact angle 15°, fiber retainer, P4	0.60095	70	110	20	49500	42570
B7014-E-T-P4S	Contact angle 25°, fiber retainer, P4	0.59893	70	110	20	46035	41085